



Made in Italy



Brema Ice Machines add a touch of elegance to your establishment. Known and trusted in the industry for high-quality construction and consistent production, they are the most reliable choice for all your ice production needs.

## Ice Flakes



**Granular System**

Brema Ice Flake Machines are used in retail, fish and seafood, and therapeutic sectors for chilled displays and presentations. The auger and ice breaker work together to create irregular shapes in a continuous fashion. The simplicity of the production process ensures cost-effective operation.



**Granular Ice,  
80-82% Dry**

## Standard Features



1L water = 1kg ice



AISI 304 Stainless steel evaporator



Air cooling system



Easy cleanable internal rounded surfaces



Dust-proof water basin



RoHS Free



Electromechanical operation



ON/OFF switch



Automatic water charge



HFC Free  
HC R290 Refrigerant Gas

## GB Series

Standard Features Included



Adjustable stainless steel feet



HCFC-Free insulated storage



Retractable insulated door



GB903A HC



GB1504A HC



### Brema Ice Machine Cleaner

For use with Brema Ice Machines to completely descale and clean interior and exterior surfaces and components. Colorless and odorless, powdered agent. Sold separately.

## G Series

Standard Features Included



1 m³ = 550 kg of ice



Rotation sensor on low speed shaft



G160A HC




G280A HC



BIN200

### GB903A HC



Adjustable feet 4 5/16" – 5 14/16"

- ① WATER IN: 3 14/16" – 6 4/16" – 3/4"
- ② WATER OUT: 1 14/16" – 5 15/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 3 7/16" – 9 1/16"

115V, 450W, 4.5A

253 lbs

209 lbs

66 lbs

26" x 19.5" x 31.5"

148 lbs

29" x 30.75" x 40"

167.5 lbs

**Power**

**Compatible With**

**Production/24h\***

**Production/24h\*\***

**Bin Capacity**


**Dimensions (L x W x H)**

**Net weight**

**Ship Dim. (L x W x H)**

**Ship weight**

### GB1504A HC



Adjustable feet 4 5/16" – 5 14/16"

- ① WATER IN: 4 2/16" – 7 3/16" – 3/4"
- ② WATER OUT: 2 1/16" – 6 14/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 3 10/16" – 10"

115V, 680W, 15A

368 lbs

335 lbs

88 lbs


27" x 29" x 36"

187 lbs

29" x 30.75" x 46.5"

209 lbs

### G160A HC



- ① WATER IN: 3 3/16" – 4 12/16" – 3/4"
- ② WATER OUT: 18 14/16" – 2 9/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 2 11/16" – 11 7/16"

115V, 665W, 5.8A

BIN100

380 lbs

368 lbs

—

22.4" x 22" x 23.6"

139 lbs

25.4" x 25.4" x 32"

163 lbs

**Power**

**Compatible With**

**Production/24h\***

**Production/24h\*\***

**Bin Capacity**


**Dimensions (L x W x H)**

**Net weight**

**Ship Dim. (L x W x H)**

**Ship weight**

### G280A HC



- ① WATER IN: 3 3/16" – 4 12/16" – 3/4"
- ② WATER OUT: 18 14/16" – 2 9/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 2 11/16" – 11 7/16"

120V, 1050W, 8.5A

BIN200

668 lbs

529 lbs

—

22" x 22" x 27.5"

183 lbs

25.5" x 25.5" x 36"

205 lbs

### BIN200

**Power**

**Compatible With**

**Production/24h\***

**Production/24h\*\***

**Bin Capacity**

**Dimensions (L x W x H)**

**Net weight**

**Ship Dim. (L x W x H)**

**Ship weight**

G280A HC

—

—


440 lbs

31" x 34" x 39.5"

163 lbs

33" x 36.25" x 47.5"

205 lbs



Adjustable feet 3 15/16" – 6 15/16"

\*Ambient Temperature  
21°C (70°F) / Water 10°C (50°F)  
\*\*Ambient Temperature  
32°C (90°F) / Water 21°C (70°F)



Intertek



Energy Verified

Warranty  
3 years parts & labor,  
5 years on the compressor