



**VERSA
HEAT**

HRG-ELC 36 SERIES ELECTRIC RANGES 36 INCHES



HRG36-12GM-4B-ELC

HRG36-12GM-4B-ELC HRG36-24GM-2B-ELC HRG36-36GM-ELC | HRG36-6B-ELC **36" ELECTRIC RANGE W/ 2, 4 OR 6 BURNERS AND/OR 12", 24" OR 36" MANUAL GRIDDLE**

- Electro-mechanical heavy-duty oven thermostat (150°F/66°C to 550°F/288°C)
- Tubular heating elements, infinite switch controlled
- Full-width pull-out stainless steel crumb tray
- Oven interior side guides & bottom porcelain-coated
- Stainless steel front and back riser and lift-off high shelf
- Stainless Steel exterior with 10" (254mm) high stainless-steel backsplash
- Cool-touch oven door handle
- Removeable, 3-position, rack guides w/1 oven rack
- 6" (152 mm) stainless steel legs are adjustable
- Also available in a 24" width version
- Requires 208 or 240 volt, 1 or 3-phase power supply


FIND
ADDITIONAL
BENEFITS
HERE



WARRANTY:
LIMITED ONE YEAR PARTS
AND LABOUR

SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT
NOTICE.

ADDITIONAL IMAGES



MODEL DESIGNATIONS

ADDITIONAL RESOURCES




DIMENSIONS

Code	Dimensions	Width		Depth		Height		Weight	
		Inches	mm	Inches	mm	Inches	mm	Lbs	KG
HRG36-12GM-4B-ELC	Exterior	36.0	915.0	30.8	782.0	59.1	1,500.0	803.4	365.2
	Shipping	39.4	1,000.0	36.6	930.0	46.9	1,190.0	479.6	218.0
	Oven Cavity	25.8	655.0	22.4	569.0	13.8	351.0		
HRG36-24GM-2B-ELC	Exterior	36.0	915.0	30.8	782.0	59.1	1,500.0	905.1	411.4
	Shipping	39.4	1,000.0	36.6	930.0	46.9	1,190.0	525.8	239.0
	Oven Cavity	25.8	655.0	22.4	569.0	13.8	351.0		
HRG36-36GM-ELC	Exterior	36.0	915.0	30.8	782.0	59.1	1,500.0	958.3	435.6
	Shipping	39.4	1,000.0	36.6	930.0	46.9	1,190.0	552.2	251.0
	Oven Cavity	25.8	655.0	22.4	569.0	13.8	351.0		
HRG36-6B-ELC	Exterior	36.0	915.0	30.8	782.0	59.1	1,500.0	701.8	319.0
	Shipping	39.4	1,000.0	36.6	930.0	43.7	1,110.0	433.4	197.0
	Oven Cavity	25.8	655.0	22.4	569.0	13.8	351.0		

TECHNICAL

Code	# of Ovens	Oven Watts	TEMP RANGE °C	TEMP RANGE °F	# of Racks	Broiler Watts	Griddle Width	Griddle Watts/ 12"	# of Burner	Watts per Burner	Voltage	Plug
HRG36-12GM-4B-ELC	1	5 kW	66°C to 288°C	150°F to 550°F	1	1.25kW	12"	4 kW	4	2 kW	208V/3P	Hard Wired
HRG36-24GM-2B-ELC	1	5 kW	66°C to 288°C	150°F to 550°F	1	1.25kW	24"	4 kW	2	2 kW	208V/3P	Hard Wired
HRG36-36GM-ELC	1	5 kW	66°C to 288°C	150°F to 550°F	1	1.25kW	36"	4 kW	-	-	208V/3P	Hard Wired
HRG36-6B-ELC	1	5 kW	66°C to 288°C	150°F to 550°F	1	1.25kW	-	-	6	2 kW	208V/3P	Hard Wired

LINE DRAWINGS



EFI Sales Ltd.
Toronto Office & DC
515 Hanlon Creek Blvd.
Guelph, ON, N1C 0A1

EFI Sales Ltd.
Vancouver Office & DC
26895 Gloucester Way
Langley, BC, V4W 3Y3

(888) 565-9920 Toll Free
(519) 822-1895 Toronto
(604) 607-8850 Vancouver