



Made in Italy




Brema Ice Machines add a touch of elegance to your establishment. Known and trusted in the industry for high-quality construction and consistent production, they are the most reliable choice for all your ice production needs.


Ice Pebbles



Brema Pebble Ice Machines are preferred in bars, pubs, restaurants and night clubs for easy-melting ice. The combined action of an auger and extruder continuously produces ice for a consistent supply. The reliability of the inner working components ensures low operating costs and high efficiency ice production.



Approximate Size



Pebble Ice,
91% Dry

Standard Features



1L water = 1kg ice



AISI 304 Stainless steel evaporator



Air cooling system



Easy cleanable internal rounded surfaces



Dust-proof water basin



RoHS Free



Electromechanical operation



ON/OFF switch



Automatic water charge



HFC Free
HC R290 Refrigerant Gas

TB Series

Standard Features Included



Adjustable stainless steel feet



HCFC-Free insulated storage



Retractable insulated door



TB852A HC



TB1404A HC



Brema Ice Machine Cleaner

For use with Brema Ice Machines to completely descale and clean interior and exterior surfaces and components. Colorless and odorless, powdered agent. Sold separately.

TM Series

Standard Features Included



1 m³ = 550 kg of ice



Frame in INOX



TM140A HC



TM250A HC




BIN110



BIN200

TB852A HC



Adjustable feet 4 5/16" – 5 14/16"

- ① WATER IN: 3 14/16" – 6 4/16" – 3/4"
- ② WATER OUT: 1 14/16" – 5 15/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 3 7/16" – 9 1/16"

120V, 500W, 4A

—

216 lbs

207 lbs

44 lbs

26" x 19.5" x 27"

130 lbs

28.25" x 21.5" x 35"

148 lbs

Power

Compatible With

Production/24h*

Production/24h**

Bin Capacity


Dimensions (L x W x H)

Net weight

Ship Dim. (L x W x H)

Ship weight

TB1404A HC



Adjustable feet 4 5/16" – 5 14/16"

- ① WATER IN: 4 6/16" – 6 14/16" – 3/4"
- ② WATER OUT: 1 15/16" – 5 2/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 6 2/16" – 8 5/16"

115V, 680W, 6A

—

333 lbs

297 lbs

88 lbs


27.2" x 29.1" x 33.5"

130 lbs

29" x 30.75" x 40"

220 lbs

TM140A HC



- ① WATER IN: 3 3/16" – 4 12/16" – 3/4"
- ② WATER OUT: 18 14/16" – 2 9/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 2 11/16" – 11 7/16"

110V, 1000W, 9A

BIN110

304 lbs

287 lbs

—

22.5" x 22" x 23.5"

139 lbs

26.25" x 25.25" x 31.75"

163 lbs

Power

Compatible With

Production/24h*

Production/24h**

Bin Capacity


Dimensions (L x W x H)

Net weight

Ship Dim. (L x W x H)

Ship weight

TM250A HC



- ① WATER IN: 3 3/16" – 4 12/16" – 3/4"
- ② WATER OUT: 18 14/16" – 2 9/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 2 11/16" – 11 7/16"

115V, 1170W, 10A

BIN200

540 lbs

500 lbs

—


22.4" x 22" x 27.4"

183 lbs

25.4" x 25.4" x 35.8"

205 lbs

BIN110



Adjustable feet 3 15/16" – 6 15/16"

—

TM140A HC

—

—

220 lbs

32" x 22" x 39.5"

117 lbs

34.5" x 24.5" x 46.25"

143 lbs

Power

Compatible With

Production/24h*

Production/24h**

Bin Capacity


Dimensions (L x W x H)

Net weight

Ship Dim. (L x W x H)

Ship weight

BIN200



Adjustable feet 3 15/16" – 6 15/16"

—

TM250A HC

—

—

440 lbs

31" x 34" x 39.5"

163 lbs

33" x 36.25" x 47.5"

205 lbs

*Ambient Temperature 21°C (70°F) / Water 10°C (50°F)
**Ambient Temperature 32°C (90°F) / Water 21°C (70°F)



Energy Verified

Warranty
3 years parts & labor,
5 years on the compressor