

## BAKERLUX SHO??rom TOUCH

Convection ovens designed for professionals that require a highly productive bakery and pastry shop. With TOUCH technology at your fingertips, they are the perfect combination of efficiency and simplicity in less than a square meter.



XAFT-04HS-ETDV



XAFT-04FS-ETDV



XAFT-04FS-ETLV



XAFT-04FS-ETRV



#### CTEAM DIV

Instantly produces humidity inside the baking chamber, for excellent results with every batch

#### AIR.Plus

Bi-directional fan(s) guarantee perfect air and heat distribution within the baking chamber for uniform results at every point throughout every tray

#### **DRY.Plus**

Humid air is expelled from the baking chamber to help the internal structure of the product form properly, creating a texture that remains perfect for hours

#### **FFFICIENT** Power

Best-in-class convection efficiency:  $60^{\circ}$ C to  $260^{\circ}$ C ( $140^{\circ}$ F to  $500^{\circ}$ F) in 5 minutes. Low-e glass lining and high-performance insulation ensure reduced energy consumption.

#### FEATURES 5

- TOUCH control panel (IPX4)
- Interior LED lighting
- 1-9 Baking steps
- Timer 0 min. to  $\infty$
- Program up to 99 recipes
- 0/20/40/60/80/100% humidity
- 2 fan speeds
- Proofer control\*
- Automatic locking door
- · Fan shut-off when door is opened
- Optional Wi-Fi & LAN connections\*

\*Proofer and Wi-Fi kits sold separately


		XAFT-04FS-ETDV	XAFT-04FS-ETLV		
DIMENSIONS	HALF SIZE (13" X 18")	FULL SIZE (18" X 26")	FULL SIZE (18" X 26")	FULL SIZE (18" X 26")	
	4	4	4	4	
SHELF CLEARANCE	3"	3"	3"	3"	
DOOR SWING	TOP TO BOTTOM	ТОР ТО ВОТТОМ	LEFT TO RIGHT	RIGHT TO LEFT	
POWER	208-240V, 3800W, 15.7A, 6-20P	208-240V, 7600W, 25.2A, 6-50P	208-240V, 7600W, 25.2A, 6-50P	208-240V, 7600W, 25.2A, 6-50P	
	1	2	2	2	
	0 - 260°C	0 - 260°C	0 - 260°C	0 - 260°C	
	32 - 500°F	32 - 500°F	32 - 500°F	32 - 500°F	
	13.75" L X 19.5" W X 13.2" H	17.4" L X 27.4" W X 13.2" H	17.4" L X 27.4" W X 13.2" H	17.4" L X 27.4" W X 13.2" H	
CHAMBER CAP.	2.0 CUFT	3.6 CUFT	3.6 CUFT	3.6 CUFT	
EXTERIOR DIM.	28.3" L X 23.6" W X 19.7" H	33.9" L X 31.5" W X 19.7" H	33.9" L X 31.5" W X 19.8" H	33.9" L X 31.5" W X 19.8" H	
NET WEIGHT	86 LBS	126 LBS	126 LBS	126 LBS	
SHIP DIM.	30.3" L X 26.8" W X 22" H	38.2" L X 44" W X 26" H	38.2" L X 44" W X 26" H	38.2" L X 44" W X 26" H	
SHIP WEIGHT	93 LBS	161 LBS	161 LBS	161 LBS	




# BAKERLUX SHORPONT TOUCH


#### CONSTRUCTION


- · Stainless steel housing & cooking chamber
- Double-pane glass door
- Insulated baking cavity for thermal efficiency and user safety



SAME DIMENSIONS FOR ETLY & ETRY MODELS.
DOOR SWINGS IN OPPOSITE DIRECTIONS







\*ETDV MODELS

### FOR ALL TOUCH MODELS:

OVEN MUST BE MIN. 2" FROM THE WALL ON BOTH SIDES (LEFT AND RIGHT).

				D						
XAFT-04HS-ETDV	23.6"	19.7"	28"	26.3"	7.3"	.7"	2.0"	.9"	4.4"	41.5"
XAFT-04FS-ETDV	31.5"	19.7"	33.9"	31.9"	7.8"	.7"	2.0"	.9"	15.7"	47.0"
XAFT-04FS-ETLV	31.5"	19.8"	33.9"	31.9"	7.8"	.7"	2.0"	.9"	15.7"	61.2"
XAFT-04FS-ETRV	31.5"	19.8"	33.9"	31.9"	7.8"	.7"	2.0"	.9"	15.7"	61.2"

ONE YEAR WARRANTY ON PARTS AND LABOR (GLASS DOOR NOT INCLUDED)









6-50P



6-20P

V1.03.2022

