



MVS 45X II (Double Bar)



| Bag Size | Capacity | Bags per Cycle |
|-----------|------------------|----------------|
| 5" x 7" | .5 pt - .5 lb | 6 |
| 6" x 8" | .5 pt - .5 lb | 6 |
| 8" x 12" | 1 qt - 2 lb | 4 |
| 10" x 12" | 1.5 qt - 3 lb | 2 |
| 10" x 15" | 3 qt - 6 lb | 2 |
| 12" x 14" | 1 gal - 8 lb | 2 |
| 12" x 16" | 1 gal - 8 lb | 2 |
| 12" x 18" | 1.25 gal - 10 lb | 2 |
| 14" x 20" | 1.75 gal - 14 lb | 2 |
| 16" x 22" | 2.5 gal - 20 lb | 2 |

| Chamber & Seal Bars | |
|--|---|
| Chamber Width x Length | 18.5" x 18" |
| Height (Chamber + Dome/Lid = Total) | 4.75" + 4" = 8.75" |
| Number of Seal Bars | 2 |
| Position of Seal Bars | Left & Right |
| Seal Bar Length | 2 x 17.75" |
| Distance between Seal Bars | 14" |
| Seal: Flat (4mm) + Bag Trimmer | ✓ |
| Unique Waffle-Pattern Sealing | ✓ |
| Hygienic Seamless Chamber | ✓ |
| Pop-Out Seal Bars | ✓ |
| Independent Power to each Seal Bar | ✓ |
| Performance | |
| Pump Type | Busch KB Oil Rotary |
| Cycles per Minute* | up to 3 |
| Free Air Displacement | 20 m ³ /h |
| Pump Power Rating | 1.25 hp |
| Power Supply | 120V / 17A |
| Display & Controls | |
| Water Resistant Digital Display | ✓ |
| LED Display | ✓ |
| Electronic Millibar Sensor | ✓ |
| Customizable Programs | 9 |
| Operational Features | |
| Programmable Sealing Time | ✓ |
| Programmable Vacuum Time (%) | ✓ |
| Extra Vacuum (30 sec) | ✓ |
| Excess Bag Cut-Off | ✓ |
| High Volume Density Plates | ✓ |
| Service | |
| Indicating Display | ✓ |
| Programmable Service Reminder | ✓ |
| 1 Year Limited Warranty | ✓ |
| Housing & Dimensions | |
| Material | Stainless 304 |
| Lid Type | Transparent with Dome |
| Width x Length | 21.25" x 24.5" |
| Height (Lid open/closed) | 31.25" / 18.5" |
| Recessed Lifting Cups | ✓ |
| Leveling Legs | ✓ |
| Shipping Wt. | 206 lbs |
| Certificates | |
| ETL Electrical |  |
| ETL Sanitation (NSF Standard) |  |
| Optional Seal Bars | |
| Liquid & Foil Bag Seal | ✓ |
| Optional Features | |
| Tray for Liquid | ✓ |
| Gentle Air Return | ✓ |
| Elevated Legs | ✓ |
| Mobile Cart | ✓ |
| Inert Gas Kit (4 Nozzles) | ✓ |
| 230V / 1ph / 9A / 20 m ³ /h | ✓ |

*Depends on type of product, film and operator ability.
Specifications may change without notice.